

This Is An Original Product From Fulham Co., Inc

Description : PONY Series, High Frequency Electronic, Rapid Start Ballast,

This Ballast Will Operate Following Lamps.




180mm T5 UV / 287mm T5 UV

ELECTRICAL DATA

INPUT VOLT: 230V ± 10%, 50/60Hz									
LAMP WATTS/TYPE	180mm T5 UV	287mm T5 UV	-	-	-	-	-	-	-
LAMPS OPERATED	1	1							
INPUT WATTS	11.40	15.77							
LINE CURRENT:	0.096	0.136							
POWER FACTOR	0.522	0.501							
BALLAST FACTOR	0.842	0.939							
EFFICACY FACTOR	7.390	5.950							
THD	157.70	165.60							
CURRENT CREST FACTOR	< 1.7								
EMI/RFI COMPLIANCE	FCC PART 18-A								
SOUND RATING	" A "								
BALLAST TYPE	RAPID START								
VOLTAGE TRANSIENTS	ANSI 62.41								
INPUT/PROTECTION	FUSE								
OUTPUT/PROTECTION	EOL								
MIN. OPERATING TEMP	0 °C (32 °F)								
MAX. CASE TEMP	75 °C (167 °F)								
APPROVALS/CLASS	cULus LISTED, CLASS " P ", 1 OUTDOOR								


MECHANICAL DATA



Where : L = Length, W = Width, H = Height

WIRING DIAGRAMS

WIRE	BLACK	WHITE	RED	BLUE	YELLOW	BROWN
LENGTH - INCHES	12 ± 1"	12 ± 1"	8 ± 1"	8 ± 1"		



Fulham extends a limited warranty only to the original purchaser or to the first user for a period of 2 years from the date of manufacture when properly installed and operated under normal conditions of use. For complete terms and conditions, please reference the Fulham product catalog (www.fulham.com)
Due to a program of continuous improvement, Fulham reserves the right to make modifications or variations in design or construction to the equipment described.