

# Low Profile LinearHO DC Modules

*Efficient, high output modules for linear applications*



- Ideal replacement for T5HO in linear highbays, vapor tights, and troffers
- Up to 219 lm/W; output range 234 lm to 14,699 lm (@4000K/80CRI)
- Aluminum extrusion mount provides superior thermal management
- Low profile design for use in smaller luminaires
- Optional lenses snap on in seconds

*Fulham's new Low Profile LinearHO DC LED modules are the powerful, efficient alternative to traditional T5HO lamps. Measuring only 0.29" high and featuring 3 SDCM LEDs, they are designed with constant current, high lumen density modules for maximum efficiency. The boards are mounted in a thin aluminum extrusion to eliminate the need for additional heatsinking. Push-in connectors allow boards to be joined with equal LED spacing across the entire length. Multiple power levels, lengths, and color temperatures make them a simple, flexible solution for luminaire manufacturers or LED retrofit projects.*

Specifications	
<b>Operating Temperature Range</b>	-40°C to 55°C / -40°F to 131°F
<b>Lumen Maintenance @105°C</b>	L70: >60,000Hrs / L90: 40,000Hrs
<b>Color Consistency</b>	Binning per ANSI C78.377-2015 @ 25°C; 3 SDCM
<b>PCB Material / Thermal Conductivity</b>	MCPCB (Aluminum Clad)/ 1.5W / mK
<b>Connector Type</b>	WAGO #2060-452 / 998-404 (2 pin connector)
<b>Warranty</b>	5 years @ Max. Tc from the date of manufacture
<b>Safety/Compliance</b>	cURus (File # E351548), UL Class 2 Lighting System, RoHS Compliant, CE, SELV

Product Models								
Model Number / Dimension (L x W x H)	Number of LED	Input Current (mA)	Nom. Fwd. Voltage (VDC)	Nom. Rated Power (W)	Max. Fwd. Voltage (V)	Max. Rated Power (W)	Nom. Lum. @4000K/80CRI (lm)	Nom. Efficacy @4000K/80CRI (lm/W)
<b>VMU048012LPyxxA</b> 5.5" x 1.26" x 0.29" 140mm x 32mm x 7mm	24	175	22.3	3.9	25	4	799	205
		350	23.1	8.1	25	9	1518	187
		480*	23.8	11.40	26	12	1959	172
<b>VMU064025LPyxxA</b> 11" x 1.26" x 0.29" 278mm x 32mm x 7mm	48	350	34.0	11.9	37	13	2347	197
		450	34.7	15.6	38	17	2942	189
		640*	35.6	22.8	39	25	3919	172
<b>VMU080030LPyxxA</b> 22" x 1.26" x 0.29" 560mm x 32mm x 7mm	60	350	33.7	11.8	37	13	2380	202
		700	35.1	24.6	39	27	4418	180
		800*	35.6	28.5	39	31	4899	172
<b>VMU125050LPyxxA</b> 22" x 1.26" x 0.29" 560mm x 32mm x 7mm	96	350	32.9	11.5	35	12	2425	211
		700	34.1	23.9	36	26	4698	197
		1250*	35.5	44.4	38	49	7700	173
<b>VMU140055LPyxxA</b> 44" x 1.26" x 0.29" 1120mm x 32mm x 7mm	108	700	33.8	23.7	36	25	4736	200
		1050	34.7	36.4	38	39	6847	188
		1400*	35.5	49.7	39	55	8656	174
<b>VMU140055LPyxxC†</b> 46" x 1.26" x 0.29" 1168mm x 32mm x 7mm	108	700	33.8	23.7	36	25	4736	200
		1050	34.7	36.4	38	39	6847	188
		1400*	35.5	49.7	39	55	8656	174
<b>VMU240095LPyxxA</b> 44" x 1.26" x 0.29" 1120mm x 32mm x 7mm	180	700	33.0	23.1	35	24	4838	209
		1400	34.2	47.9	37	52	9331	195
		2400*	35.6	85.4	39	94	14,699	172
<b>VMU240095LPyxxC†</b> 58" x 1.26" x 0.29" 1473mm x 32mm x 7mm	180	700	33.0	23.1	35	24	4838	209
		1400	34.2	47.9	37	52	9331	195
		2400*	35.6	85.4	39	94	14,699	172

**VMU048012LPyxxA**


Color Temperature  
 30 = 3000K  
 35 = 3500K  
 40 = 4000K  
 50 = 5000K

CRI  
 8 = 80  
 9 = 90 (Made to order)

\* Indicates maximum rated current. Modules may be operated at a current less than or equal to this value, below the Tc rating.

† Made to order. Minimum order quantity applies.

Accessories			
Model Number	Description	Model Number	Description
<b>TLEOPT120-002</b>	5.5" snap-on lens, 82% transmissivity	<b>TLEOPT120-013</b>	44" snap-on lens, 82% transmissivity
<b>TLEOPT120-003</b>	11" snap-on lens, 82% transmissivity	<b>TLEOPT120-014</b>	46" snap-on lens, 82% transmissivity
<b>TLEOPT120-004</b>	22" snap-on lens, 82% transmissivity	<b>TLE-OPT-120-021</b>	58" snap-on lens, 82% transmissivity
<b>TLC-HN02</b>	22" wire harness for 1 or 2 modules in parallel	<b>TLC-HN04</b>	22" wire harness for 3 or 4 modules in parallel



**FULHAM** [www.fulham.com](http://www.fulham.com)

North America • China • Europe • India • Latin America • Middle East

Fulham Headquarters: 12705 S. Van Ness Avenue, Hawthorne, CA 90250 Tel: +1 (323) 599-5000 Fax: +1 (323) 754-9060 • order@fulham.com

All trademarks are the property of their respective owners | ©Fulham Co. Inc., 2018 | PN: FLYER-LED-LPLHO | REV: AUG18