



# TECHNICAL DATA SHEET : ELECTRONIC BALLAST

Project : STANDARD

Type : ECONOMIC

Model No : HSC-240-136-UT8-OAA

Remark :

## Model : 1 x 36W BALLAST



## Input Characteristics

1	Voltage (Un)	240 Vac
2	Operating Voltage Range	140 ~ 277 Vac
3	Frequency (Hz)	50 / 60 Hz
4	Current (A)	0.16 A
5	Wattage (W)	36W
6	Power Factor (PF)	> 0.94 (PPFC)
7	Current Harmonics (Athd)	< 35%
8	Over Current Protection	Yes
9	Surge Withstanding Capacity	Yes
10	Over Voltage Application	@ 320Vac 48Hrs & @ 360Vac 2Hrs

## Output Characteristics

1	Lamp Types	36W-T8-FTL 40W-T12-FTL 36W-PLL
2	Number of Lamps	1
3	Lamp Connection	Single
4	Lamp Current	0.320A
5	Operating Frequency	≥ 40KHz
6	Ignition Method	RS

## Ballast Characteristics

1	Lamp Current Crest Factor (CCF)	≤ 1.90
2	Ballast Efficiency (BE)	≥ 86%

## Protection Features

1	Deactivated Lamp	NO
2	Restart or Latching	N/A

## Environmental Operating Details

1	Minimum Lamp Starting Temperature	0°C
2	Max. Ambient Temperature	50°C
3	Max. Case Temperature (Tc)	65°C

## Ordering Information

Sr No	Model Number	Description	Case Lot
1	HSC-240-136-UT8-OAA	1x36W T8 <35% THD 1x40W T12 <35% THD 1x36W PLL <35% THD	180

## Mechanical Details

1	Weight	75 gm
2	Case Dimensions	
	Length W/Mount	172 mm
	Center to Center (CTC)	167 mm
	Width	30.5 mm
	Height	25.5 mm
3	Case Material	ABS
4	Wiring Diagram	On Screen
5	Input / Output Connections	Connectors, Screw Type
6	Wires Length & Colors	
	Input (White & Black)	N/A
	Output (White)	N/A
	Output (Gray)	N/A
7	Potting	N/A

## Notes

A High power factor Electronic ballast specially designed for heavy duty use.

### Key features :-

- Compact Design with Low Height
- Lower losses.
- High Voltage Resistance
- High Surge Protection
- Long Life
- High Durability
- Plastic body (No Earthing Required)
- Most Economical
- Lamp will not Shut down @ high Voltage