

Description: 3 W Linear LED Module / 370X12mm / 10LEDs / S5 P2


This LED Module Should be Operated On:

Any LED Driver designed to Provide output Current of 100mA and Voltage 30Vdc

ELECTRICAL DATA

NOMINAL INPUT VOLTAGE (V _{DC})	30
NOMINAL INPUT CURRENT (mA)	100
NOMINAL POWER CONSUMPTION(W)	3
PCB SIZE (mm)	LINEAR 500 x 12MM
PCB MATERIAL TYPE	FR-4
CCT	6500K / 5700K / 4000K
CALCULATED USABLE ARRAY FLUX (lm)	500 / 500 / 500
RECOMMENDED ATTACHMENT METHOD	M3 Pan Head Screw
WEIGHT (gm)	40
MAXIMUM STORAGE TEMPERATURE (°C)	-40 to 100
MAXIMUM OPERATING AMBIENT TEMPERATURE (°C)	-40 to 50
MAXIMUM T _c (°C)	75
BEAM ANGLE	120°
CRI (Typ)	80


MECHANICAL DATA



PCB SIZE=370X12MM

SYM	DIAM	TOL	QTY	NOTE
+	3.000 mm		3	
TOTAL			3	

WIRING DIAGRAMS



Driver must be grounded (if applicable).

Fulham extends a limited warranty only to the original purchaser or to the first user for a period of 3 years from the date of manufacture when properly installed and operated under normal conditions of use. For complete terms and conditions, please reference the Fulham product catalog (www.fulham.com)
Due to a program of continuous improvement, Fulham reserves the right to make modifications or variations in design or construction to the equipment described. © Fulham Company Limited, All Rights Reserved.