

Represented By

DATE

1

1

Job Name

Job Number

# Digital to Analog 0-10V Adaptor

CA-AA-DZT-CTC-T CA-AA-DZT-PWM-T



## Overview

The digital-to-analog 0-10V adapter enables integration of analog 0-10V controlled lighting with Fulham's digital control system. Additionally, the adapter interfaces with contact closures which allows for switches and other contact closure devices to integrate with the control a

This adapter is ideal for controlling LED drivers as well as fluorescent and compact fluorescent ballasts using analog 0-10V control. Leveraging Fulham's digital control system's flexibility, the adapter can be installed to meet your needs. The adapter can be configured for individual fixture control and installed within a fixture, for zone control of a group of fixtures and installed in a convenient location or any configuration in between.

These capabilities make the digital to analog adapter ideal for general control applications requiring analog control including office space, class-rooms, warehouses, conference rooms, lobbies and hallways.

### Features

#### Summary

- Enables digital control of analog devices and systems
- Provides digital presicion and individual addressing capabilities to analog systems
- Small form factor
- Class 2 wiring (no power line connection)
- Does not require external power source, bus powered
- Compatible with standard DALI controllers
- 5 year limited warranty


#### Analog Control Devices

- Enables digital control of analog systems for I ED
- Fluorescent
- CFL
- Contact closure (switch input) 0-10V compliant systems
- Controls up to 25 fixtures
- Ideal for projects requiring analog lighting control in office space, classrooms, warehouses, conference rooms, lobbies, and hallways.

## **Flectrical Data**

| MAX OPERATING TEMP    | 65°C (149°F)   |
|-----------------------|--|
| MIN OPERATING TEMP    | -20°C (-4°F)   |
| POWER SOURCE          | DALI bus   |
| OPERATING VOLTAGE     | 9.5-22.5 VDC   |
| CURRENT DRAW          | 2 mA   |
| 0-10V CONTROL OUTPUT  | Controls up to 25 fixtures (50 mA)                                       |
| CONTACT CLOSURE INPUT | Internal pull-up 3.3V (330uA -dry contact)                               |
| CERTIFICATIONS        | UL 916 Listed, FCC 47CFR Part 18 & 15, RoHS Compliant                    |
|                       | C62.41 Cat. A Transient Protection, Class A Sound Rating, DALI Compliant |

# Mechanical Information



Fulham extends a limited warranty only to the original purchaser or to the first user for a period of 5 years from the date of manufacture when properly installed and operated under normal conditions of use. For complete terms and conditions, please reference the Fulham product catalog (www.fulham.com) Due to a program of continuous improvement, Fulham reserves the right to make modifications or variations in design or construction to the equipment described. 2012-346 Rev B