

## SPECIFICATION SHEET: WH41-UNV-L

This Is An Original Product From Fulham Co., Inc

**Description: WORKHORSE Electronic Ballast.** 


Parallel Lamp Operation.


\* This Ballast Will Operate The Following Lamp Types:

CFQ/4P, CFTR/4P, T5, T6SL, T8, T8SL, CFT/4P, FT/4P, T9CR, T5CR, T5HO, T10, T12, T12SL. WHEN USED PER FULHAM'S LAMP/BALLAST WIRING DIAGRAM.

## **ELECTRICAL DATA (Universal.120 - 277V)**

INPUT VOLT: 120V - 277V ± 10%, 50/60Hz		
LAMP TYPE AND	1	CFQ/4P, CFTR/4P, T5, T6SL, T8, CFT/4P, FT/4P, T9CR, T5CR, T5HO, T10, T12, T12SL
NUMBER OF LAMPS	2	CFQ/4P, CFTR/4P, T5, T8.
WIRING DIAGRAM#	REFER TO FULHAM'S LAMP / BALLAST WIRING DIAGRAM.	
POWER FACTOR	HIGH POWER FACTOR	
THD	< 10% @ FULL POWER	
EMI/RFI COMPLIANCE	FCC PART 18-A	
SOUND RATING	"A"	
BALLAST TYPE	INSTANT START	
VOLTAGE TRANSIENTS	ANSI C82.11 - 1993 / C62.41	
MIN. OPERATING TEMP	0 °C ( 32 °F )	
MAX. CASE TEMP	70 °C ( 158 °F )	
APPROVALS/CLASS	UL LISTED, CLASS " P ", 1 OUTDOOR	
* NOTE:	PLEASE CONTACT FULHAM CUSTOMER SERVICES FOR PERTICULAR LAMP/BASLLAST SPECIFICATIONS.	





Fulham extends a limited warranty only to the original purchaser or to the first user for a period of 5 years from the date of manufacture when properly installed and operated under normal conditions of use. For complete terms and conditions, please reference the Fulham product catalog (www.fulham.com) Due to a program of continuous improvement, Fulham reserves the right to make modifications or variations in design or construction to the equipment described.

2014-464 Rev A