

Fulham seeks to continually provide high quality and dependable products built on solid technology platforms. It occasionally becomes necessary to end the life of products due to changes in the market and technology improvements.

This letter announces the Product Discontinuance (PD) plan for the following **LED MODULES**. The last date to order these products will be March 22, 2019 unless stock is depleted sooner.

We are available and ready to discuss your specific business needs associated with this announcement in order to minimize any potential impact. For further assistance, please contact your Fulham sales representative, or Fulham Client Services (323-599-5000) or order@fulham.com.

ITEM #	DESCRIPTION
TM32RD0527-201	32 LED Module - Round - FR4 - 8.8W - 2700K - 80 CRI - conn
TM32RD0530-201	32 LED Module - Round - FR4 - 8.8W - 3000K - 80 CRI - conn
TM32RD0535-201	32 LED Module - Round - FR4 - 8.8W - 3500K - 80 CRI - conn
TM40HR0527-201	40 LED Module - Half Round - FR4 - 350mA - 500mA (Max) Constant Current - 36-37 VDC Forward Voltage - 10.9 - 16W - 2700K - (size: 7" Diameter) - 1,695 Lumens - 80 CRI - w/ dual connector
TM40HR0530-201	40 LED Module - Half Round - FR4 - 350mA - 500mA (Max) Constant Current - 36-37 VDC Forward Voltage - 10.9 - 16W - 3000K - (size: 7" Diameter) - 1,800 Lumens - 80 CRI - w/ dual connector
TM40HR0535-201	40 LED Module - Half Round - FR4 - 350mA - 500mA (Max) Constant Current - 36-37 VDC Forward Voltage - 10.9 - 16W - 3500K - (size: 7" Diameter) - 1,870 Lumens - 80 CRI - w/ dual connector
TM40HR0540-201	40 LED Module - Half Round - FR4 - 350mA - 500mA (Max) Constant Current - 36-37 VDC Forward Voltage - 10.9 - 16W - 4000K - (size: 7" Diameter) - 1,950 Lumens - 80 CRI - w/ dual connector
TM40HR0550-201	40 LED Module - Half Round - FR4 - 350mA - 500mA (Max) Constant Current - 36-37 VDC Forward Voltage - 10.9 - 16W - 5000K - (size: 7" Diameter) - 2,085 Lumens - 80 CRI - w/ dual connector
TM40RD0527-001	40 LED Module - Round - 11W - 2700K - (size: 7" Diameter)
TM40RD0527-201	40 LED Module - Round - FR4 - 350mA - 500mA (Max) Constant Current - 31-32 VDC Forward Voltage - 10.9 - 16W - 2700K - (size: 7" Diameter) - 1,695 Lumens - 80 CRI - w/ dual connector
TM40RD0530-201	40 LED Module - Round - FR4 - 350mA - 500mA (Max) Constant Current - 31-32 VDC Forward Voltage - 10.9 - 16W - 3000K - (size: 7" Diameter) - 1,800 Lumens - 80 CRI - w/ dual connector
TM40RD0530-211	40 LED Module - Round - FR4 - 350mA - 500mA (Max) Constant Current - 31-32 VDC Forward Voltage - 10.9 - 16W - 3000K - (size: 7" Diameter) - 1,800 Lumens - 90 CRI - w/ dual connector
TM40RD0535-201	40 LED Module - Round - FR4 - 350mA - 500mA (Max) Constant Current - 31-32 VDC Forward Voltage - 10.9 - 16W - 3500K - (size: 7" Diameter) - 1,870 Lumens - 80 CRI - w/ dual connector
TM40RD0540-201	40 LED Module - Round - FR4 - 350mA - 500mA (Max) Constant Current - 31-32 VDC Forward Voltage - 10.9 - 16W - 4000K - (size: 7" Diameter) - 1,950 Lumens - 80 CRI - w/ dual connector
TM40RD0550-201	40 LED Module - Round - FR4 - 350mA - 500mA (Max) Constant Current - 31-32 VDC Forward Voltage - 10.9 - 16W - 5000K - (size: 7" Diameter) - 2,085 Lumens - 80 CRI - w/ dual connector
TM40RD0627-201	40 LED Module - Round - 11.4W - 2700K - (size: 7" Diameter) - w/Conn
TM40RD0630-201	40 LED Module - Round - 11.4W - 3000K - (size: 7" Diameter) - w/Conn
TM40RD0640-201	40 LED Module - Round - FR4 - 350mA - 11.4W - 4000K - (size: 7" Diameter) - dual wire connector

TM40RT0527-201	40 LED Module - Rectangular - FR4 - 500mA (Max) Constant Current - 31.5 VDC Forward Voltage - 11W - 2700K - size: 4" x 6" - 1,800 Lumens - 80 CRI - w/ dual connector
TM40RT0530-201	40 LED Module - Rectangular - FR4 - 500mA (Max) Constant Current - 31.5 VDC Forward Voltage - 11W - 3000K - (size: 4" x 6") - 1,800 Lumens - 80 CRI - w/ dual connector
TM40RT0530-206	40 LED Module - Rectangular - FR4 - 350mA - 500mA (Max) Constant Current - 36-37 VDC Forward Voltage - 10.9 - 16W - 3000K - (size: 4" x 7"x.22"H) - 1,800 Lumens - 80 CRI - w/ dual connector
TM40RT0530-211	40 LED Module - Rectangular - 11W - 3000K - (size: 4" x 6") - 90 CRI
TM40RT0535-201	40 LED Module - Rectangular - FR4 - 500mA (Max) Constant Current - 31.5 VDC Forward Voltage - 11W - 3500K - (size: 4" x 6") - 1,800 Lumens - 80 CRI - w/ dual connector
TM40RT0540-201	40 LED Module - Rectangular - FR4 - 500mA (Max) Constant Current - 31.5 VDC Forward Voltage - 11W - 4000K - (size: 4" x 6") - 1,950 Lumens - 80 CRI - w/ dual connector
TM40RT0540-206	40 LED Module - Rectangular - FR4 - 350mA - 500mA (Max) Constant Current - 36-37 VDC Forward Voltage - 10.9 - 16W - 4000K - (size: 4" x 7"x.22"H) - 1,950 Lumens - 80 CRI - w/ dual connector
TM40RT0550-201	40 LED Module - Rectangular - FR4 - 500mA (Max) Constant Current - 31.5 VDC Forward Voltage - 11W - 5000K - (size: 4" x 6") - 1,950 Lumens - 80 CRI - w/ dual connector
TM64RD0527-201	64 LED Module - Round - FR4 - 350mA - 1,050mA (Max) Constant Current - 22.2 - 25.2 VDC Forward Voltage - 7.8W - 26.5W - 2700K - (size: 9" Diameter) - 2,785 Lumens - 80 CRI - w/ dual connector
TM64RD0530-201	64 LED Module - Round - FR4 - 350mA - 1,050mA (Max) Constant Current - 22.2 - 25.2 VDC Forward Voltage - 7.8W - 26.5W - 3000K - (size: 9" Diameter) - 2,975 Lumens - 80 CRI - w/ dual connector
TM64RD0535-201	64 LED Module - Round - FR4 - 350mA - 1,050mA (Max) Constant Current - 22.2 - 25.2 VDC Forward Voltage - 7.8W - 26.5W - 3500K - (size: 9" Diameter) - 3,075 Lumens - 80 CRI - w/ dual connector
TM64RD0540-201	64 LED Module - Round - FR4 - 350mA - 1,050mA (Max) Constant Current - 22.2 - 25.2 VDC Forward Voltage - 7.8W - 26.5W - 4000K - (size: 9" Diameter) - 3,200 Lumens - 80 CRI - w/ dual connector
TM64RD0550-201	64 LED Module - Round - FR4 - 350mA - 1,050mA (Max) Constant Current - 22.2 - 25.2 VDC Forward Voltage - 7.8W - 26.5W - 4000K - (size: 9" Diameter) - 3,425 Lumens - 80 CRI - w/ dual connector
TM64RD0650-201	64 LED Module - Round - FR4 - 17.6W - 5000K - (size: 9" Diameter) - 80 CRI - Conn
TM80RD0527-201	80 LED Module - Round - FR4 - 1,050mA (Max) Constant Current - 27.8 - 31.5 VDC Forward Voltage - 9.7W - 33W - 2700K - (size: 9" Diameter) - 3,475 Lumens - 80 CRI - w/ dual connector
TM80RD0527-211	80 LED Module - Round - FR4 - 22.1W - 2700K - (size: 9" Diameter) - 90 CRI - w/DW Connector
TM80RD0530-201	80 LED Module - Round - FR4 - 1,050mA (Max) Constant Current - 27.8 - 31.5 VDC Forward Voltage - 9.7W - 33W - 3000K - (size: 9" Diameter) - 3,700 Lumens - 80 CRI - w/ dual connector
TM80RD0530-211	80 LED Module - Round - FR4 - 22.1W - 3000K - (size: 9" Diameter) - 90 CRI - w/DW Connector
TM80RD0535-201	80 LED Module - Round - FR4 - 1,050mA (Max) Constant Current - 27.8 - 31.5 VDC Forward Voltage - 9.7W - 33W - 4000K - (size: 9" Diameter) - 3,840 Lumens - 80 CRI - w/ dual connector
TM80RD0535-211	80 LED Module - Round - FR4 - 22.1W - 3500K - (size: 9" Diameter) - 90 CRI - w/DW Connector
TM80RD0540-201	80 LED Module - Round - FR4 - 1,050mA (Max) Constant Current - 27.8 - 31.5 VDC Forward Voltage - 9.7W - 33W - 4000K - (size: 9" Diameter) - 4,000 Lumens - 80 CRI - w/ dual connector
TM80RD0540-201C	80 LED Module - Round - FR4 - 1,050mA (Max) Constant Current - 31.5 VDC Forward Voltage - 17.6W - 4000K - (size: 9" Diameter) - 4,000 Lumens - 80 CRI - w/ dual connector & conformal coating
TM80RD0540-211	80 LED Module - Round - FR4 - 22.1W - 4000K - (size: 9" Diameter) - 90 CRI - w/DW Connector

TM80RD0550-201	80 LED Module - Round - FR4 - 1,050mA (Max) Constant Current - 27.8 - 31.5 VDC Forward Voltage - 9.7W - 33W - 4000K - (size: 9" Diameter) - 4,275 Lumens - 80 CRI - w/ dual connector
TM80RD0627-201	80 LED Module - Round - FR4 - 22.8 - 34.1W - 2700K (size: 9" Diameter) - w/DW connector
TM80RD0630-201	80 LED Module - Round - FR4 - 22.8 - 34.1W - 3000K (size: 9" Diameter) - w/DW connector
TM80RD0640-201	80 LED Module - Round - FR4 - 22.8 - 34.1W - 4000K (size: 9" Diameter) - w/DW connector